

RATCLIFF STEP LIFT RANGE

RATCLIFF PALFINGER



ONE, TWO AND THREE STEP MODELS LIFTING 300KG PROVIDING SAFER WHEELCHAIR ACCESS

Ratcliff Step lifts are unique. They are designed so that able-bodied and disabled people can use the same entrance. The lift stows as steps and is easily deployed to give a full-sized platform to provide safe wheelchair access.

The three models permit step lifts to be fitted up to a maximum vehicle floor height of 1300mm. Used frequently in mobile libraries and health units. Also ideal for 'mobile' offices and consultation areas such as police stations, fire incident rooms, exhibition units etc.



RATCLIFF STEP LIFTS RS300/1, RS300/2, RS300/3 - 300KG CAPACITY

SUITABLE FOR MOBILE LIBRARIES, HEALTH UNITS, EXHIBITION UNITS, OFFICES ETC



Unique design

Step lifts are designed so that able-bodied and disabled people can use the same entrance. The lift stows as steps and is easily deployed to give a full-sized platform (top/middle right).

Safer Wheelchair Access

When deployed part of the platform is inside the vehicle, thus requiring less space than traditional passenger lifts, providing safer wheelchair access.

3 Models to fit wide range of vehicle heights

A one step lift (top left), a two step lift (middle left) and a three step lift (bottom left).

Detachable Ramp

All lifts have a detachable ramp for ease of going on and coming off the platform. (middle right)

Hi Viz Wheelchair Stop Bar

Prevents the wheelchair rolling off the platform. (bottom right)

Anti-Slip Surfaces

The two and three step lifts have ribbed-rubber platform surface and high visibility striping to step edges. The one step lift has an aluminium treadplate surface.

Toe-Trap Cut Bar

All models have a toe trap cut bar which automatically stops the lift if the passenger's foot goes over the bar, to prevent injury.

High Viz Hand Rails

All models have fixed yellow high visibility handrails to assist regular and wheelchair entry.



model	platform dimensions (width x depth)	max floor height	min door aperture width	overall internal width	cut in depth required to chassis	distance between steps (excl. 1st step)	min weight
RS300/3	1270 x 820	1000*	1020	1155	690	215	160kg
RS300/2	1200 x 760	750	1020	1155	610	200	155kg
RS300/1	1200 x 760	650	1020	1155	680	varies	145kg

* consult Ratcliff for floor heights over 1000mm

all measurements shown in mm unless otherwise stated

For further information on these products or other lift models

Please contact the RATCLIFF PALFINGER Sales Office on +44 (0)1707 382880 or a member of the Sales Team for assistance

The RATCLIFF PALFINGER policy is one of continuous product development and the Company therefore reserves the right to alter product or component specifications without notice

RATCLIFF PALFINGER

RATCLIFF PALFINGER Ltd

Bessemer Road
Welwyn Garden City
Hertfordshire AL71ET, United Kingdom
Tel: +44 (0)1707 325571 - Fax: +44 (0)1707 327752
Info@ratcliffpalfinger.co.uk

Subject to setting and printing errors

www.ratcliffpalfinger.co.uk

