



Scope of delivery

Basic data		Weights	
Order number:	600017568	Gross weight:	0 / 0
Vehicle number:	41S2919	1. Front axle:	0 / 0
Vehicle variant:	TGS 35.470 8X4 BL	2. Front axle:	0 / 0
Type of vehicle:	missing text (vehicle_type:	3. Front axle:	0 / 0
Basic vehicle:	L41S SU 37	Leading axle:	0 / 0
Status:	In production	1. Rear axle:	0 / 0
Planned delivery date:	3/4/20	2. Rear axle:	0 / 0
		Trailing axle:	0 / 0

Add/remove	Code	Description
------------	------	-------------

Current scope of delivery

	001AA	steering arrangement, left
	005UW	Wheelbase 1795+4105+1350 mm
	006EG	rear frame overhang 1050 mm
	018V2	Engine D2676LF79 - 470 hp / 346 kW EURO6 SCR - 2,400 Nm C-R OBD-D
	021HF	Gearbox software for road deployment (TipMatic PROFI Performance)
	022QE	MAN TipMatic® 12 28 OD gearbox
	023JD	Fuel tank 400l right and 35l AdBlue
	025MG	front axle VOK-09/VOK-09, dropped
	026EF	front springs parabolic 9,5 t
	027AN	radiator and intercooler for up to 35 degrees ambient temperature
	028MP	Rear springs, air, 2x11.5 t
	029GC	Propshafts for high load profile
	02AAG	Instrument panel km/h 'High-Line in colour'
	030EE	steering wheel with height and inclination adjustment
	032AB	MAN BrakeMatic (electronic brake system)
	034NM	hypoid rear axle HYD-1370/HY-1350
	035ET	Hypoid axle ratio i = 3.70
	037AC	with differential lock in rear axle
	038GH	disc wheels 10 hole 11.75-22.5 on 1st FA TL
	038JH	disc wheels 10-hole11.75-22.5 on 2nd front axle TL
	038PG	disc wheels 10-hole 9.00-22.5 on 1st RA TL
	038RG	disc wheels 10-hole 9.00-22.5 on 2nd RA TL
	038XT	without spare wheel

Add/remove	Code	Description
	03KAA	fuel tank fitted
	042EK	Digital tachograph DSRC; made by CONTI
	050NF	L cab 2240mm wide, 2280mm long
	052AC	Storage box accessible from inside and outside - flap unlocked from inside
	058BA	seat coverings in standard quality
	058NH	driver's seat, high-comfort, with air suspension
	059NE	co-driver's seat static, with longitudinal, seat back and height adjustment
	05NAE	front panel unlockable from inside
	080AF	door interior panelling fabric
	116AE	visco fan
	118EK	Short mounting base (engine only)
	118MA	EDC engine regulation
	118TG	Engine operating temperature range, moderate climates
	119EH	General PTO parameterisation
	122J4	PTO NTX/10b with flange f=1.38 below
	124AI	Fuel filter for fuels up to Cleanliness Class 21
	124AW	Fuel pre-filter (oil separator/water trap) with mixing valve and water sensor
	128EC	Pressure sensor for air spring bellows
	142AD	Preparation of remote download data interface for digital tachograph
	142AF	calibrate tachograph
	150MC	Window cleaning set
	150WR	Brushed aluminium insert on instrument panel
	153EY	air auxiliary heater EBERSPÄCHER D4S
	153KA	air conditioning system AC R134A without CFHC
	159XS	without cab insulation NORDIC (against cold) for M, L and LX cab
	194AD	operator's manual in GERMAN
	201AS	air intake raised with dry air filter
	201FA	fine dust and pollen filter
	203EK	connection for external engine speed control (ZDR)
	203EU	Control module for external data exchange (customer-specific control module) with fleet management system interface 2.0 (FMS), body functionality
	205CL	1-cylinder air compressor, 360 ccm with economy system
	206BV	qUL: Exhaust system relocated
	206KB	Exhaust on right with bottom outlet
	208AL	regulated rocker arm brake (EVBec)
	208EA	MAN PriTarder
	210XX	Without flame-start/jump-start system
	211FD	Single-disc clutch DBE 430

Add/remove	Code	Description
	212AA	gearbox shift lock, pneumatic
	227AC	rear axle breather upswept
	230AH	rear underride guard, round
	230ER	front underride guard
	230FC	lateral guard
	232HA	synthetic bumper with integrated airdam
	236AF	cross member for trailer coupling
	241AC	without platform mounting brackets
	245XX	without spare wheel holder
	256AF	steering wheel lock with immobiliser
	256EA	emergency steering pump
	258HA	anti-lock braking system (ABS)
	258NA	ECAS air suspension
	259CA	disc brake for front axle
	259CB	disc brake for rear axle
	262XX	without brake connection on frame end
	265AF	Parking brake with pneumatic application of front wheel brakes
	272FA	Entry lighting for driver and co-driver
	280DC	qUL: Flat cab roof, straight, lowered by 190 mm, L cab
	280EC	Fly mesh guard before radiator
	280HD	Engine start/stop device under front panel
	2800E	QRC: rear frame overhang
	2800U	qUL: Offset battery box
	283FS	Cab mounts on coil springs for 'L,LX ,XL,XLX,XXL' cab
	28KSB	qUL: Fuel tank relocated
	280AA	qUL: adjustment of sunblind in front of windscreen
	280AG	qUL: adjustment of revolving beacon on cab roof
	280AJ	Qualified conversion supplier: Adaptation of antenna for radio
	280AN	Qualified conversion supplier: Adaptation of red/white interior lighting in cab roof
	280AP	qUL: Adaptation of antenna for digital radio reception (DAB+)
	280AT	Qualified conversion supplier: Adaptation of clearance lamps
	280AU	Qualified conversion supplier: Adaptation of stowage compartment above windscreen
	28QAB	qUL: AdBlue tank relocated
	28QCK	Qualified conversion supplier: CO2 characteristic data for MAN Individual scope
	28QDV	qUL: Compressed air tank offset
	28QFE	qUL: Without vent flap in cab roof
	28QGW	qUL: propshaft

Add/remove	Code	Description
	28QKV	Qualified conversion supplier: Fuel pre-filter relocated
	28QMD	Qualified conversion supplier: Applicable documents
	28QPS	qUL: parametrisation for special-purpose vehicles
	28QRA	qUL: Frame attachments
	28ZAZ	qUL: Wheelbase
	303AX	Lockable tank fastener - 1 u. ventilated for master key system
	303CC	AdBlue lockable filler cap 1 pc.
	309AA	Beam throw regulator
	310EE	Halogen twin headlights H7 for right-hand traffic
	310HQ	LED daytime driving lights (ECE R87-compliant)
	310LH	Red/white interior lighting in cab roof
	310PA	cable harness for taillights 1.5 m, delivered loose
	311PE	Automatic lowering of the air suspension to rubber/metal buffer with residual pressure control
	311PK	ECAS parameter entry with additional circuit for suppressing the automatic levelling suspension system
	318AI	LED clearance lamps
	318AK	lateral marker lights
	319AR	reading lamp for driver
	321EC	Central locking
	324AC	Two-tone horn,electric
	325AA	MAN Tronic (on-board computer)
	325EA	Language 1 'German' for display in instrument panel
	325HB	provision for toll recording system 'TollCollect'onboard unit (dashboard fitting)mat.provided and owned by TC
	326FZ	Socket in cab 12V 2-pole and 24V 2-pole
	326XY	Without 12/24 V socket on end of frame
	327AF	Battery main switch, mechanical
	329CT	Two 12-V 175-Ah batteries
	329ER	Battery box up to 175 Ah
	329HC	Maintenance sign for batteries - 'maintenance-free'
	331AB	Basic alternator
	339FP	Display on the dashboard for operating data
	345AS	Maximum electronic speed limitation 90 km/h
	345EA	Cruise control
	346CA	charging pressure indicator
	350AB	MAN sound system
	350IW	Connectivity Board module (RIO Box)
	350JE	Video function via USB/SD interface
	350JM	MAN media package Navigation

Add/remove	Code	Description
	350NP	MAN Media Truck Advanced radio, 12 V with seven-inch colour display and preparation for navigation
	3500R	SD card, navigation system, WHOLE OF EUROPE
	350PB	DAB+ digital radio reception
	350TQ	Hands-free functionality 'Comfort' for two mobile phones (multi-function steering wheel and Bluetooth®-capable)
	351ME	MAN CameraView - preparation for rear-view camera (one camera)
	351US	AUX-IN/USB in the instrument panel
	352DX	2 LED revolving beacons on cab roof, left and right
	352WS	Revolving beacon, yellow
	362AH	Stabiliser on both rear axles
	363AA	Stabiliser for front axle
	366CA	Reinforced shock absorber for front axle
	370CR	Air dryer, heated
	373AE	antifreeze effective down to -35 degrees
	376FA	1 bunk with storage space (with aluminium frame).
	376HA	Mattress for lower bunk
	376KA	Bunk cover for bottom bunk
	376XK	Without Mattress for upper bunk
	380AC	Windscreen of laminated glass tinted
	380CA	Door windows tinted
	381AA	Cab rear wall without windows
	381CE	All-roand curtain
	381CM	Diagonal curtain
	384CD	Safety belt display, driver's side
	385AT	Side windows tinted behind B-post
	386AS	Mechanical lifting roof
	387AF	Electric door window lifters for driver and co-driver
	388AH	Roller blind for windscreen, mechanical
	388AK	Sun shade in front of windscreen
	389AC	handles left and right (on B-post)
	389AD	handles left and right (on A-post)
	390AG	Oddments tray in door armrest
	390CT	cup holder in dashboard
	390CU	1 pull-out drawer in centre of dashboard
	390XB	without pigeon hole on rear wall
	390XX	without oddment box
	392AH	kerb mirror, right
	392CL	EU front mirror on co-driver's side

Add/remove	Code	Description
	392CZ	Electrically heated and adjustable rear view mirror, heated wide-angle mirror
	392HA	Mirror brackets for body width 2500-2600 mm width 2500 mm
	400AH	mudflap front
	401CY	synthetic mudguards, 3-part, with mud flaps
	401EL	3-part synthetic mudguards for 2nd front axle
	404AP	spray reducer
	405AC	Bonding set, separate
	405AK	hazard-warning sign
	405AR	Hazard-warning lamp
	407XX	Without jack
	411AF	2 chocks
	417AC	wheel bolt covers front
	434CH	Smoking package
	434DB	Interior design in Urban Concrete
	44VCA	Crankcase ventilation closed
	538AF	Carpeted engine tunnel
	542DH	National registration documentation Germany
	542FC	anti-noise package 80 dB (92/97EEC)
	542KY	Noise value corresponds to ECE51.03 Phase 2
	542NC	Registration as N3 vehicle, (GVW > 12t)
	600AC	Fittings for right-hand traffic
	796BB	Conversion order to qualified MAN Truck & Bus SE converter from Central Sales
	798BY	TÜV acceptance (modification / CSR)
	798LF	Height over cab, unloaded up to 4000 mm
	798RA	Body mounting/conversion in acc. with Truck Request. TR number:
	798WP	Modification not part of basic homologation (CoC); note national registration requirements

Nationale Baugruppe

Nationale Subbaugruppe

	DEA04	MAN Fahrerjacke
	DEA19	Auslieferungspaket: Technische Einweisung im Servicestützpunkt (nach Aufbaufertigstellung)
	DEDT3	DTCO personalisieren - Einfügen der Halterdaten, Amt.. Kennzeichen etc.
	DEP01	Motor vehicle registration certificate
	DETR2	Transportpauschale Schwere Reihe

Wheel

Front axle

		2 x WA 385/55R22,5 LENK-NAH TL 160& K
--	--	---------------------------------------

Front axle 2

Add/remove Code Description

2 x WA 385/55R22,5 LENK-NAH TL 160& K

Rear axle

4 x WA 315/80R22,5 ANTR-S+G TL 154/150 K

Rear axle 2

4 x WA 315/80R22,5 ANTR-S+G TL 154/150 K

Colour

chassis

graphite black RAL 9011 matt - Water

wheels

White aluminium acrylic RAL 9006 - Normal

cab

Pure white RAL 9010 - Normal