

To whom it may concern

Krefeld, 15.06.2021

Dear Sir or Madam,

## YOUR ENQUIRY FOR A PALFINGER ACCESS PLATFORM

Thank you very much for your enquiry and your interest in our products and services. We are pleased to support you during the evaluation process to find the right access equipment for safe operations in heights. Based on the information we received we are glad to provide you with a non-binding quotation for:

### **PALFINGER Access Platform P 280 CK mounted on MAN TGL 8.190 4x2**

PALFINGER stands for the most innovative lifting solutions at the highest technological level. With PALFINGER Access Platforms you invest in safe and reliable height access technology that is of outstanding quality.

PALFINGER is the only manufacturer in the world offering both non-insulated and insulated access platforms reaching working heights from 10m to 103m for chassis weights between 3.5t and 60t GVW. PALFINGER Access Platforms are thus optimally adjusted to the relevant working range.

We always strive to provide the best service and support to our customers. So in case of questions or remarks please do not hesitate to contact us. However, we are convinced that our quotation will meet your expectations and take the liberty of contacting you in this regard.

Yours sincerely,  
**PALFINGER PLATFORMS GMBH**

Michael Gruböck  
Sales & Service Manager EMEA

i.A.  
Andrea Grabensee  
Inside Sales Manager EMEA

Quotation for

# **PALFINGER P 280 CK**

mounted on MAN TGL 8.190 4x2



Picture shows additional equipment. For reference only.

Date: 15.06.2021

**PALFINGER PLATFORMS GMBH**  
Düsseldorfer Str. 100  
47809 Krefeld | Germany

# CONTENT

Price Overview	4
Your Scope of Supply	4
Our Recommended Additional Equipment and Services	6
Terms and Conditions	7
Your Required Basic Specification	8
Our Recommended Add. Equipment	10

# PRICE OVERVIEW

## YOUR SCOPE OF SUPPLY

Item	Qty	Description	
P 280 CK	1	PALFINGER Access Platform P 280 CK	
MXLKW-MAN	1	MAN TGL 8.190 4x2, WB3900mm, Euro 6d	
ABW00103	1	Bordering 300mm, both sides hinged	
ABW02001	1	Attachment point for load securing nets	
AHA01003	1	Bracket 7 traffic cones (without cones)	
ALO00201	1	4 lashing pints at platforms covering	
ATG00	1	Dividing plate at boom rest (+ bracket)	
DDK00101	1	Operating instructions, stickers German	
EED00101	1	Display in addition to the control panel	
EIS00301	1	Insulation package	
ELB00111	1	4 working lights at basic frame	
ELW00123	1	Flashing light; fixed left on turntable	
ELW00124	1	Flashing light; fixed right on turntab.	
ESC00125	1	Emergency control, display at basis	
ESC00206	1	Memory function	
FAT00108	1	Modifications at truck chassis / 8	
KWZ00102	1	Tool storage tray, 500 mm	
SSG00101	1	Protection guard on top of driver's cab	
SSR00102	1	2 Covers for warning beacon on turntable	
KOST13	1	Large aluminium workman cage	

## OUR RECOMMENDED ADDITIONAL EQUIPMENT AND SERVICES

(Note: The items shown below are not included in the above-mentioned price!)

Item	Qty	Description	Price (EUR)

# TERMS AND CONDITIONS

**Terms of delivery**

Free carrier (FCA) according to Incoterms® 2020, Löbau. All prices are net prices with VAT excluded.

**Validity of pricing**

---

**Terms of payment**

To be agreed upon.

**Delivery time**

To be agreed upon.

**Terms and conditions of business**

According to our General Terms and Conditions of Business which can be found at <https://www.palfinger.com/en-gb/terms-conditions>. Of course we will be pleased to provide you with the required document upon request.

We reserve the right to make technical alterations without prior notice. Illustrations may differ.

Please take your time to carefully check this quotation. Furthermore, please check if the described machine meets the registration requirements in your country as we cannot assume any liability for local restrictions that may apply.

# YOUR REQUIRED BASIC SPECIFICATION

P 280 CK	PALFINGER Access Platform P 280 CK as per technical description
MXLKW-MAN	MAN TGL 8.190 4x2, wheelbase 3900mm, CC cab, emission class Euro 6d, GVW 7490kg
ABW00103	Bordering 300mm high, on the platform decking as part of the chassis covering, hinged at right and left hand side with gap between bordering and platform decking
ABW02001	Attachment point for load securing nets at the bordering
AHA01003	Bracket for 7 traffic cones (without traffic cones)
ALO00201	4 clevis mounted inside the chassis covering
ATG00	Dividing screen with bracket at the mainboom rest and in the cage. Including brackets in the possible additional ordered cages
DDK00101	Operating instructions, stickers, labels and display messages (if display available) in German language
EED00101	Display in addition to the control panel
EIS00301	Insulation package: Double insulation against 1000V according to DIN VDE 0682-742. The insulation is effective only, if a fiberglass cage is mounted.
ELB00111	4 working lights mounted at the basic frame to illuminate the outrigger areas; switch inside the driver's cab
ELW00123	Flashing light; yellow; fixed; on the left side at the turntable; Type Comet-B LED
ELW00124	Flashing light; yellow; fixed; on the right side at the turntable; Type Comet-B LED
ESC00125	Electronic emergency control of the platform via display at the base. Inclusive height limitation; height and PIN are freely programmable
ESC00206	Memory function (for Light NX only in conjunction with display EED00101)
FAT00108	Modifications at truck chassis / 8
KWZ00102	Tool storage tray integrated in the cage; 500 mm long
SSG00101	Protection guard on top of driver's cab (made of wave grid)
SSR00102	2 Covers for warning beacon on turntable
KOST13	Large aluminium workman cage (width 1,800mm x length 700mm x height 1,100mm), designed for 3 persons, replaces the standard cage, including load cell, max. permissible cage load 300kg, outreach is reduced