

MBB C 500 VAN FLEX

THE FOLDABLE LIFT WITH 500 KG LIFTING CAPACITY

MBB C 500 VAN FLEX

LIFETIME EXCELLENCE

MBB C 500 VAN FLEX THE VERTICAL FOLDABLE PANEL VAN LIFT


MBB C 500 VAN FLEX

- For all panel vans
- Fast and easy installation
- Always access to the right rear door
- Cylinder integrated in lifting gear
- Bridge plate as standard

LOAD DIAGRAM

- Innovative platform stabilizer with step tread
- Lighted registration plates
- Removable ball-head coupling optionally available
- Roll stops (max. 2 x 450 mm) as option
- 600 kg load capacity on request

WEIGHTS



MBB C 500 VAN FLEX			
Q (kg)			
500			
430			
360			
260			

Platform type	Depth (mm)	Width(mm)	Weight (kg)
Aluminium	1400	1575	from 160
Platform folded	690		

* Optional up to 1850 mm

TECHNICAL DATA


Lifting capacity	500 kg (600 kg optional)
Main beam	120 x 80 mm
Lifting gear hydraulics	1 x lifting cylinder / 1 x tilting cylinder
Platform overlap with floor	510 mm
Lift arm pitch	600 mm
Load centre - longitudinal	100 mm off-centre, 50 % rated load one-sided
Load centre - across centre	+90° to -10°

500

DIMENSIONS

Lift arms (in mm)

H (max.) Loading height unloaded*	780
H (min.) Loading height loaded*	450
F (max.) middle of main beam to upper edge of loading floor	340
K (min.) at dimension F (max.)	546
D (min.) Installation space (min.)	814 (926)



AVAILABLE FOR

- Mercedes-Benz Sprinter (906 / 907)
- Volkswagen Crafter und MAN TGE
- Iveco Daily
- Citroen Jumper / Fiat Ducato / Peugeot Boxer
- Ford Transit
- Renault Master / Opel Movano / Nissan NV 400
- Further vehicles on request



PALFINGER TAIL LIFTS GmbH

Fockestraße 53 27777 Ganderkesee Germany www.palfinger.com



Applications shown in the leaflet do not always correspond to the standard specifications. Design and specification are subject to change without prior notice. Country specific regulations must be considered for the tail lift installation. Dimensions may vary. Subject to technical changes, errors and translation mistakes.