

MBB C 1500 SK


MBB C 2000 SK



- For motor vehicles with a low-mount coupling system
- For the high demands in food and beverage logistics, for example
- Lifting capacity 1,500/2,000 kg with 1,000 mm load distance in each case
- Four-cylinder lifting mechanism with long lifting arm for level installation
- Tilttable, single-piece underide guard (mechanical or hydraulic, depending on type)
- Design with aluminium or steel platform
- Extremely wide range of special equipment available

LOAD DIAGRAM


MBB C 1500 SK		MBB C 2000 SK	
a (mm)	Q (kg)	a (mm)	Q (kg)
1,000	1,500	1,000	2,000
1,250	1,200	1,250	1,600
1,500	1,000	1,500	1,330
1,750	850	1,750	1,140
2,000	750	2,000	1,000



CLOSE-COUPLED VEHICLES WITH 1,500 / 2,000 KG LIFTING CAPACITY

WEIGHTS

Aluminium platform type	
Platform width (mm)	2,500
Platform height (mm)	
2,100	703 kg
2,200	714 kg
2,300	725 kg
Steel platform type	
Platform width (mm)	2500
Platform height (mm)	
2,009	811 kg
2,109	861 kg



DIMENSIONS

Lifting arm lengths (mm)	700	800	900	1,000	1,100
H (max.) loading height, unloaded	1,200	1,428	1,528	1,651	1,793
H (min.) loading height, loaded	883	916	1,006	950	1,023
F (max.) middle of main beam to upper edge of loading floor	650	817	924	977	1,056
K (min.) at dimension F (max.)	618	601	623	721	783
D (min.) installation dimension, minimum	768	751	773	871	933
F (min.)	508	566	614	569	608
K (max.) at dimension F (min.)	726	820	907	1,040	1,132
D (max.) installation dimension, maximum	876	970	1,057	1,190	1,282

TECHNICAL DATA

Type	MBB C 1500 S
Lifting capacity	1,500 kg
Main beam	180 x 180 mm
Lifting gear hydraulics	2 lifting cylinders / 2 tilting cylinders
Platform overlap with floor	-63 mm
Lifting arm pitch	1,300 mm
Load centre, longitudinal	1,000 mm
Load centre, across centre	Central, 50% of rated load on one side
Inclination angle of the platform	+90° to -10°

Some of the tail lifts pictured feature special customer-specific equipment. Country-specific regulations must be considered for the tail lift installation. Dimensions may vary. Subject to technical changes, errors and translation mistakes.

