

SCANIA

PK 24.001 SLD5

P 410 B6X2*4

CONTRACT NUMBER: PALDRIVE 266

NEW

AVAILABLE



SPECIFICATION

VEHICLE HANDOVER WITHIN 14 DAYS FROM OFFICIAL ORDER.



PK 24.001 SLD5

| | |
|-----------------------|----------|
| lifting moment | 23,1 mt |
| max. outreach | 14,8 m |
| max. lifting capacity | 4.900 Kg |
| swivel range | 400° |



SCANIA P 410 B6X2*4

| | |
|-----------------------|--------------|
| construction year | 2022 |
| main Axle distance | 5.150 mm |
| power | 410 Hp |
| Scania warranty until | october 2024 |



MCC-INSTALLATION

OFFER INFORMATION

Location details

PALFINGER, 86-050 - Poland

Dealer Name

Palfinger EMEA GmbH PL

Availability

Available

Product type

New

Contract number

Paldrive 266

Dealer E-mail

sales@palfinger.com

Dealer phone

004366488345792

| | |
|------------------------|-----------|
| Platform length | 7,0 m |
| loading height | 1,2 m |
| max. payload | 11.500 Kg |

PRODUCT

| | | | |
|--------------------------|----------------|---------------------------------|------------------|
| Manufacturer | Palfinger | Lifting moment | 23,1 mt |
| Model | PK 24.001 SLD5 | Outreach / Lifting power | 14,8m / 1.180 Kg |
| Construction year | 2022 | Max outreach | 14,8 m |

TRUCK

| | | | |
|---------------------------|----------|-----------------------------|--------------------|
| Truck manufacturer | SCANIA | Axes | 6*2*4 |
| Construction year | 2022 | Gross vehicle weight | 26.000 Kg |
| Drivers cabine | CP20L | Dead weight | 14.500 Kg |
| Wheel base | 5.150 mm | Payload | 11.500 Kg |
| Power | 410 PS | Payload category | 6t - 15t |
| Emmission standard | EURO 6 | Construction | Crane and platform |

PK 24.001 SLD5**SCANIA P 410 B6X2*4****HYDRAULIC & TECHNICS**

- Hydraulic 5 extension
- High-speed extension system with return oil recovery
- Swivel range 400°
- Hydraulic support leg extension (max.support width 5,600mm)
- Rigid support legs
- Hose equipment for two additional devices

ASSISTANCE SYSTEMS

- Paltronic 40
- HPSC-E
- CPS-L (cabin protection)

EQUIPMENT

- Scanreco radio remote control - 6 linear functions
- LED-working light on the articulated arm
- 8.0to load hook
- Painting RAL3020
- hydraulic oil tank 200l

SPECIFICATION

- 410 Hp, torque max. 2.150 Nm
- Automatic gearbox: GR875 + opticruise
- main axle distance 5.150mm
- air suspension on all axles
- Fuel tank 400l / AD-Blue 80l
- Tires 1st and 2nd and trailing axles 385/55 R22.5
- Drive axle tires 315 / 70 R22.5
- Cabin color: Ivory-White / chassis color: Subgrey
- Cab type: CP20L
- Auxiliary heating: WTA cab + engine heater 6 kW

MCC-INSTALLATION**OVERVIEW**

- Crane installation front
- PALFINGER Modular low built platform
- platform dimensions in the clear: w=2.480 mm ; l=7.000 mm
- platform border profile 45° beveled with lashing points approx. every 170 mm
- floor made out of 27mm thick plywood
- frontwall height 1.500mm inclusive gallery for lifting equipment + two working lights
- side- & rearwall height 800mm

- two heavy duty toolboxes
- Storage depot for poles/wood
- six working lights and two reversing lights in total
- Underrun protection - manually extendable by 670mm
- Plastic - single axle mudguards (round)

