

SCANIA

PK 24.001 SLD5 P 420 B6X2*4 NB







SPECIFICATION

PK 24.001 SLD5

- Hydraulic 5-fold extension
- High-speed extension system with return oil recovery
- Swivel range 400°
- Hydraulic support leg extension (max.support width 5,600mm)
- Rigid support legs
- Support leg extension 200 mm
- Paltronic 40
- HPSC-E + LOAD
- Transport monitoring crane and support
- Scanreco radio remote control 6 functions with cross levers
- Painting RAL3020

Prior sale and changes reserved!

OFFER INFORMATION

Location details PALFINGER, 86-050 - Poland

Dealer Name



Availability

Available

Product type New

Contract number Paldrive 438

Dealer E-mail sales@palfinger.com

Dealer phone 004366488345792



- Working lights on the articulated arm
- Hose equipment for two additional devices
- 8.0t load hook

Platform

- internal dimensions 7.000mm x 2.480mm
- Multifunctional Frontwall height: 1500 mm
- Side and rear wall height: 750 mm
- Left and right 2 folding steps each
- 6 rows of lashing rails integrated in the floor
- Flat bottom 27mm plywoodplates

SCANIA P 420 B6x2*4 NB

- 420 HP
- Air suspension on all axles
- Fuel tank 355l / AD-Blue 80l
- Tires 1st and trailing axle 385/65 R22.5
- Drive axle tires 315/80 R22.5
- Cabin color: Ivory White / Chassis color: Sub Grey



PRODUCT

| Manufacturer | Palfinger | Lifting moment | 20,9 mt |
|-------------------|----------------|--------------------------|---------------------|
| Model | PK 24.001 SLD5 | Outreach / Lifting power | 14,8m / 1.040 Kg |
| Construction year | 2023 | Max outreach | 14,8m |
| | | Max Outreach | 14,011 |

TRUCK

| Truck manufacturer | SCANIA | Axes | 6*2*4 |
|--------------------|----------|----------------------|--------------------|
| Construction year | 2023 | Gross vehicle weight | 26.000 Kg |
| Drivers cabine | CP20L | Dead weight | 14.400 Kg |
| Wheel base | 5.100 mm | Payload | 11.600 Kg |
| Power | 410 HP | Payload category | 6t - 15t |
| Emmission standard | EURO 6 | Construction | Crane and platform |