

GSR

IVECO

P 200 AXE-E SMART PLUS IVECO MY2024 GSR

NEW

IN PRODUCTION

SYMBOLFOTO



SPECIFICATION

- Lightweight and compact double articulated aerial platform for working in confined spaces, installed on a 3.5 t lorry.


The double pantograph ensures great versatility and the ability to overcome obstacles at height.

- Multifunction electric controls for greater precision, speed and manoeuvring comfort
- Vertical stabilisation with extendable front crossbars to better compensate for uneven ground and slopes.
- Platform with three stabilisation options for all working conditions:
 - In profile: for maximum compactness in confined spaces.
 - With front crossbars extended: for maximum performance when working at height.
 - Partial stabilisation: for maximum performance with minimum space requirements.

STANDARD

OFFER INFORMATION

Location details

Modena, 41122 - Italy 

Dealer Name

Palfinger srl

Product type

New

Dealer E-mail

info@palfingerplatformsitaly.it

v.dalcamo@palfinger.com

Dealer phone

0039059252426

GSR

- Mechanical cab/boom anti-collision system
- Hydraulically rotating basket 90° right + 90° left
- Machine operating hour meter
- Mouth-extension protection cap
- Inclinator with audible and visual alarm for aerial working conditions
- Air/water line from the column to the basket
- Extended distribution plates to be placed under the stabilisers with relative housings on the platform
- 12V socket on the basket
- 230V / 16A or 110V / 16A electrical socket in the basket
- Cataphoresis painting, PALFINGER patented KTL system
- Aerial part centring display for machine closure
- Provision for insulation.

CONFIGURATION:

Aluminium cage

Home function

Kit 4.0

Boom colour: white RAL 9016

Basic Version truck (without driver airbag and air conditioning)

Check the configuration with the sales department

P 200 AXE-E Smart Plus Iveco IVECO MY2024
GSR

PRODUCT

Manufacturer	PALFINGER	Turret rotation	370°
Model	P 200 AXE-E Smart Plus	Basket size	1.4 x 0.84 x h 1.1 m
Construction year	2025	Basket capacity	250 kg
Outreach	8,20 m	Basket turning device	90+90
Max. height of work	19,7	Basket material	alu

TRUCK

Truck manufacturer	IVECO	Axes	4x2
Emmission standard	EURO 6 E	Gross vehicle weight	3500 Kg