

### MAN

PK 24.001 SLD5 TGS 28,520 6X4-4 + KH **CONTRACT NUMBER: PALDRIVE 382** 





## **SPECIFICATION**

### Crane: PK 24.001 SLD5

- Hydraulic 5-fold extension
- High-speed extension system with return oil recovery
- Swivel range 400°
- Hydraulic support leg extension (max.support width 6,600mm)
- Support leg extension 100mm
- support legs 180° tiltable
- Paltronic 40
- HPSC-E + LOAD
- Scanreco radio remote control (2-2-2) cross levers
- Painting RAL3020
- Working lights on the articulated arm

# OFFER INFORMATION

Location details MCC-NORTH SOLEC, 86-050 - Poland

Dealer Name



Availability Available

Product type New

Contract number Paldrive 382

Dealer E-mail sales@palfinger.com

Dealer phone 004366488345792



- Hose equipment for two additional devices including quick coupling (multi-faster)

- 8.0to load hook

### Superstructure: Tipper (KH Kipper)

- Inner dimensions 4,350 x 2,440 mm
- front wall height 1200 mm
- side wall height 800 mm
- Floor tipping bridge made of 5 mm Hardox
- Lashing rings in the floor panel and front wall

- Rear wall divided, upper part swingable and removable, lower part with 300 mm hydr. rock flap made of steel

#### **Chassis: MAN**

- TGS 28.520 6x4-4 BL CH
- 520 Hp / 2.650 Nm
- Leaf suspension front axle, air suspension on both rear axles
- Fuel tank 300I / AD-Blue 35I
- Tires front 385/65/R22.5
- Tires rear 315/80/R22.5

- Cabin color: Traffic White RAL9016 / Chassis color: Graphite Black RAL9011

- trailer coupling RINGFEDER Typ RF40/G150B



# PRODUCT

Manufacturer	Palfinger	Lifting moment	23,1 mt
Model	PK 24.001 SLD 5	Outreach / Lifting power	14,8m / 1180Kg
Construction year	2023	Max outreach	14,8 m
TRUCK			
Truck manufacturer	MAN	Axes	6x4
Construction year	2023	Gross vehicle weight	26.000 Kg
Drivers cabine	NN	Dead weight	15.700 Kg
Wheel base	3.600+1.400 mm	Payload	10.300 Kg
Power	520 HP	Payload category	6t - 15t
Emmission standard	EURO 6e	Construction	Crane and tipper