

IVECO

P 240 AXE- E SMART PLUS IVECO 35 S 14 MY2024 GSR

NEW

SYMBOLFOTO

IN PRODUCTION



SPECIFICATION

- Lightweight and compact double articulated aerial platform for work in tight spaces, mounted on a 3.5 t truck.
 - The double pantograph unit guarantees great versatility and the ability to move over in elevated positions.
 - Multifunction electric controls for greater precision, speed, and manoeuvring comfort
 - Vertical stabilisation with frontwards extending outriggers which compensate for uneven and sloping ground
 - Platform with three stabilisation options for all working conditions:
1. Within the outer vehicle limits: for maximum compactness overall within small spaces
 2. With front crossmembers extended: for maximum performance when working in elevated positions

OFFER INFORMATION

Location details

Modena, 41122 - Italy 

Dealer Name

Palfinger srl

Product type

New

Dealer E-mail

info@palfingerplatformsitaly.it

v.dalcamo@palfinger.com

Dealer phone

0039059252426

MY2024 GSR

3. Partial stabilisation: for maximum performance with minimum overall dimensions.

STANDARD

- 12V socket on basket
- 230V / 16 socket A or 110V / 16A 12V socket on basket
- 40 l diesel tank
- Aerial section centring display for aerial part closing
- Air/water line from the column to the basket
- Anti-collision system cab/boom
- Cage rotation 90°+ 90°
- Hour meter
- Inclinator with audio alarm signal and signal lights relating to aerial work conditions
- Painting with cathaphoresis process, with KTL system patented by PALFINGER
- Preparation for insulation upgrade ability
- Set of 4 spreader plates with proper housing on the chassis
- Top boom protection.



P 240 AXE- E Smart Plus Iveco IVECO 35 S 14
MY2024 GSR

PRODUCT

Manufacturer	PALFINGER	Turret rotation	290°
Model	P 240 AXE-E Smart Plus	Basket size	1.4 x 0.84 x h 1.1 m
Construction year	2025	Basket capacity	250 kg
Outreach	11,60 m	Basket turning device	90+90
Max. height of work	22,9 m	Basket material	aluminio

TRUCK

Truck manufacturer	IVECO	Emmission standard	EURO 6
Construction year	2025	Axes	4x2
Wheel base	3450 mm	Gross vehicle weight	3500 Kg