

Meiller

MAN

**PK 24.001 SLD5**

**TGS 28.520 6X4-4 + MEILLER**

CONTRACT NUMBER: PALDRIVE 383

NEW

AVAILABLE



## SPECIFICATION

### Crane: PK 24.001 SLD5

- Hydraulic 5-fold extension
- High-speed extension system with return oil recovery
- Swivel range 400°
- Hydraulic support leg extension (max.support width 6,600mm)
- Support leg extension 100mm
- support legs 180° tiltable
- Paltronic 40
- HPSC-E + LOAD
- Scanreco radio remote control (6L) linear levers
- Painting RAL3020
- Working lights on the articulated arm

## OFFER INFORMATION

Location details

MCC-NORTH SOLEC, 86-050 - Poland 

Dealer Name

Palfinger EMEA GmbH PL

**PALFINGER**

Availability

Available

Product type

New

Contract number

Paldrive 383

Dealer E-mail

sales@palfinger.com

Dealer phone

004366488345792

## Meiller

---

- Hose equipment for two additional devices including quick coupling (multi-faster)

- 8.0t load hook

### **Superstructure: Tipper (Meiller)**

- Inner dimensions 4,600 x 2,440 mm

- front wall height 1200 mm

- side wall height 800 mm

- Floor tipping bridge made of 5 mm Hardox

- Lashing rings in the floor panel and front wall

- Rear wall divided, upper part swingable and removable, lower part with 300 mm hydr. rock flap made of steel

### **Chassis: MAN**

- TGS 28.520 6x4-4 BL CH

- 520 Hp / 2.650 Nm

- Leaf suspension front axle, air suspension on both rear axles

- Fuel tank 300l / AD-Blue 35l

- Tires front 385/65/R22.5

- Tires rear 315/80/R22.5

- Cabin color: Traffic White RAL9016 / Chassis color: Graphite Black RAL9011

- trailer coupling RINGFEDER Typ RF40/G150B

All pictures taken from a reference project.

Meiller

**PRODUCT**

|                          |                 |                                 |                   |
|--------------------------|-----------------|---------------------------------|-------------------|
| <b>Manufacturer</b>      | Palfinger       | <b>Lifting moment</b>           | 23,1 mt           |
| <b>Model</b>             | PK 24.001 SLD 5 | <b>Outreach / Lifting power</b> | 14,8m /<br>1180Kg |
| <b>Construction year</b> | 2023            | <b>Max outreach</b>             | 14,8 m            |

**TRUCK**

|                           |                   |                             |                  |
|---------------------------|-------------------|-----------------------------|------------------|
| <b>Truck manufacturer</b> | MAN               | <b>Axes</b>                 | 6x4              |
| <b>Construction year</b>  | 2023              | <b>Gross vehicle weight</b> | 26.000 Kg        |
| <b>Drivers cabine</b>     | NN                | <b>Dead weight</b>          | 15.700 Kg        |
| <b>Wheel base</b>         | 3.600+1.400<br>mm | <b>Payload</b>              | 10.300 Kg        |
| <b>Power</b>              | 520 HP            | <b>Payload category</b>     | 6t - 15t         |
| <b>Emmission standard</b> | EURO 6e           | <b>Construction</b>         | Crane and tipper |