

PAL Pro 39 Mechanics Truck Ford 2018 Ford



F-550 XL

FORD

PAL PRO 39 MECHANICS TRUCK

2018 FORD F-550 XL

STOCK NUMBER: C56410


MECHANICS TRUCK

AVAILABLE



OFFER INFORMATION

Location details

145 E, 350 N Fwy Service Rd, Fairfield, TX, 75840 -
United States 

Dealer details

Freestone Chrysler Jeep Dodge | Contact: Heather
Schick

Dealer E-mail

heather@freestonechryslerjeepdodge.com

Dealer phone

1-903-390-2978

Availability

Available

Product type

Mechanics Truck

Stock number

C56410

CRANE BODY TECHNICAL DETAILS

- 44" standard compartment heights with 60" raised compartment on curbside
- 11' Mechanics body
- Treadplate cargo floor, load space walls and compartment tops
- Hybrid torsion box and ladder frame
- Palfinger engineered internal gussets prevents body cracking
- Full length channel drip rails
- Double panel doors with internal C-channel stiffeners, adhered with structural adhesive
- Non-marring boom rest

SERVICE CRANE TECHNICAL DETAILS

- PSC 6025H Hydraulic crane
25' Reach
Momentum rating 38,500 Ft/lbs
- Wireless Remote Standard
 - 400 degree Rotation
 - 6000# Capacity
 - WINCH Hydraulic planetary winch standard for speed, durability, and higher duty cycle. Boom mounted winch for consistent line length when raising or lowering boom.
 - E-Coat Process

[PSC 6025 Brochure Download](#)

- Workbench featuring 21" bumper, receiver hitch, 1/4" steel top plate and thru compartment
- Linear adjustable front mounts
- Aluminium doors and hinges
- Rubber mounted LED lights
- E-coat primer
- Full Hydraulic Outriggers up and down/out

[PAL Pro 39 Brochure Download](#)

[COMPRESSOR TECHNICAL DETAILS](#)

Palfinger PRC 45v Rotary screw air compressor:

-45 CFM @ 150 PSI

-100% duty cycle

-Cold Start Protection

[CHASSIS DETAILS](#)

- 2018 Ford D-550 Chassis XL Truck Regular Cab

F-550 XL

-200 PSI Air pressure relief

valve

-Automatic air pressure

blowdown

-Integrated hydraulic oil and

air coolers

-High temperature shutdown

-Limited Lifetime warranty

-1/2" x 50' Air hose reel

located in curbside rear

vertical compartment and

routed through rear wall with

guide

-1/2" moisture separator/

regulator/oiler

-6 Gallon air reservoir

mounted between frame rails

at rear