

PAL Pro 39 Mechanics Truck Ram 2018 Ram



5500 Tradesman

RAM

PAL PRO 39 MECHANICS TRUCK 2018 RAM 5500 TRADESMAN

STOCK NUMBER: 218889

MECHANICS TRUCK

AVAILABLE



OFFER INFORMATION

Location details

145 E, 350 N Fwy Service Rd, Fairfield, TX, 75840 -
United States

Dealer details

Freestone Chrysler Jeep Dodge | Contact: Heather
Schick

Dealer E-mail

heather@freestonechryslerjeepdodge.com

Dealer phone

1-903-390-2978

Availability

Available

Product type

Mechanics Truck

Stock number

218889

5500 Tradesman

CRANE BODY TECHNICAL DETAILS

PAL Pro 39

- 44" standard compartment heights with 60" raised compartment on curbside
- 11' Mechanics body
- Treadplate cargo floor, load space walls and compartment tops
- Hybrid torsion box and ladder frame
- Palfinger engineered internal gussets prevents body cracking
- Full length channel drip rails
- Double panel doors with internal C-channel stiffeners, adhered with structural adhesive
- Non-marring boom rest

SERVICE CRANE TECHNICAL DETAILS

Palfinger 6025H Hydraulic

crane 25' Reach

Momentum rating 38,500 Ft/lbs

- Wireless Remote Standard
- 400 degree Rotation
- 6000# Capacity
- WINCH Hydraulic planetary winch standard for speed, durability, and higher duty cycle. Boom mounted winch for consistent line length when raising or lowering boom.
- E-Coat Process

[PSC-6025 Brochure Download](#)

5500 Tradesman

- Workbench featuring 21" bumper, receiver hitch, 1/4" steel top plate and thru compartment
- Linear adjustable front mounts
- Aluminium doors and hinges
- Rubber mounted LED lights
- E-coat primer
- Full Hydraulic Outriggers up and down/out

[PAL Pro 39 Brochure Download](#)

COMPRESSOR TECHNICAL DETAILS

Palfinger PRC 45v Rotary screw air compressor:
-45 CFM @ 150 PSI
-100% duty cycle
-Cold Start Protection

CHASSIS DETAILS

- 2018 Ram 5500 Tradesman Chassis Regular Cab

-200 PSI Air pressure relief
valve

-Automatic air pressure
blowdown

-Integrated hydraulic oil and
air coolers

-High temperature shutdown

-Limited Lifetime warranty

-1/2" x 50' Air hose reel
located in curbside rear
vertical com-partment and
routed through rear wall with
guide

-1/2" moisture separator/
regulator/oiler

-6 Gallon air reservoir
mounted between frame rails
at rear