

ISUZU

P 240 AXE- E SMART PLUS M21 EURO 6 DEF

NEW

SYMBOLFOTO IN PRODUCTION



SPECIFICATION

- Lightweight and compact double articulated aerial platform for work in tight spaces, mounted on a 3.5 t truck.
- The double pantograph unit guarantees great versatility and the ability to move over in elevated positions.
- Multifunction electric controls for greater precision, speed, and manoeuvring comfort
- Vertical stabilisation with frontwards extending outriggers which compensate for uneven and sloping ground
- Platform with three stabilisation options for all working conditions:
- 1. Within the outer vehicle limits: for maximum compactness overall within small spaces
- With front crossmembers extended: for maximum performance when working in elevated positions

OFFER INFORMATION

Location details Modena, 41122 - Italy

Dealer Name Palfinger srl

Product type New

Dealer E-mail info@palfingerplatformsitaly.it v.dalcamo@palfinger.com

Dealer phone 0039059252426



 Partial stabilisation: for maximum performance with minimum overall dimensions.

STANDARD

- 12V socket on basket
- 230V / 16 socket A or 110V / 16A 12V socket on basket
- 40 I diesel tank
- Aerial section centring dispaly for aerial part closing
- Air/water line from the column to the basket
- Anti-collision system cab/boom
- Cage rotation 90°+ 90°
- Hour meter
- Inclinometer with audio alarm signal and signal lights relating to aerial work conditions
- Painting with cataphoresis process, with KTL system patented by PALFINGER
- Preparation for insulation upgrade ability
- Set of 4 spreader plates with proper housing on the chassis
- Top boom protection.

CONFIGURATION:

- Aluminium cage
- Home function
- Boom color: white RAL 9016

Please, verify the configuration with sales office



PRODUCT

| Manufacturer | PALFINGER | Turret rotation | 370° |
|------------------------|---------------------------|-----------------|-------------------------|
| Model | P 240 AXE-E Smart Plus | Basket size | 1.4 x 0.84 x h 1.1 m |
| Construction year | 2023 | Basket capacity | 250 kg |
| - | | Basket turning | 90+90 |
| Outreach | 11,60 m | device | |
| Max. height of work | 22,9 m | Basket material | alu |

TRUCK

| Truck manufacturer | ISUZU | Emmission standard | EURO 6 D DEF |
|--------------------|---------|----------------------|--------------|
| Wheel base | 2500 mm | Axes | 4x2 |
| | | Gross vehicle weight | 3500 Kg |