

MAN

PK 24.001 SLD5

TGS 28.520 6X4-4 + KH

CONTRACT NUMBER: PALDRIVE 380

NEW

AVAILABLE



SPECIFICATION

Crane: PK 24.001 SLD5

- Hydraulic 5-fold extension
- High-speed extension system with return oil recovery
- Swivel range 400°
- Hydraulic support leg extension (max.support width 6,600mm)
- Support leg extension 100mm
- support legs 180° tiltable
- Paltronic 40
- HPSC-E + LOAD
- Scanreco radio remote control (6L) linear levers
- Painting RAL3020
- Working lights on the articulated arm

OFFER INFORMATION

Location details

MCC-NORTH SOLEC, 86-050 - Poland 

Dealer Name

Palfinger EMEA GmbH PL **PALFINGER**

Availability

Available

Product type

New

Contract number

Paldrive 380

Dealer E-mail

sales@palfinger.com

Dealer phone

004366488345792

- Hose equipment for two additional devices including quick coupling (multi-faster)
- 8.0to load hook

Superstructure: Tipper (KH Kipper)

- Inner dimensions 4,350 x 2,440 mm
- front wall height 1200 mm
- side wall height 800 mm
- Floor tipping bridge made of 5 mm Hardox
- Lashing rings in the floor panel and front wall
- Rear wall divided, upper part swingable and removable, lower part with 300 mm hydr. rock flap made of steel

Chassis: MAN

- TGS 28.520 6x4-4 BL CH
- 520 HP / 2.650 Nm
- Leaf suspension front axle, air suspension on both rear axles
- Fuel tank 300l / AD-Blue 35l
- Tires front 385/65/R22.5
- Tires rear 315/80/R22.5
- Cabin color: Traffic White RAL9016 / Chassis color: Graphite Black RAL9011
- trailer coupling RINGFEDER Typ RF40/G150B
- selectable all-wheel-drive

PRODUCT

| | | | |
|-------------------|-----------------|--------------------------|-------------------|
| Manufacturer | Palfinger | Lifting moment | 23,1 mt |
| Model | PK 24.001 SLD 5 | Outreach / Lifting power | 14,8m / 1180Kg |
| Construction year | 2023 | Max outreach | 14,8 m |

TRUCK

| | | | |
|--------------------|-------------------|----------------------|------------------|
| Truck manufacturer | MAN | Axes | 6x4 |
| Construction year | 2023 | Gross vehicle weight | 26.000 Kg |
| Drivers cabine | NN | Dead weight | 15.700 Kg |
| Wheel base | 3.600+1.400 mm | Payload | 10.300 Kg |
| Power | 520 HP | Payload category | 6t - 15t |
| Emmission standard | EURO 6e | Construction | Crane and tipper |